

SPEC		Mini box (IMT-M648)
Main Processor & Basic Components	CPU	Amlogic S905X ARM's Cortex-A53 Quad-Core 1.5GHz
	Video	H.265 HEVC MP-10 up to 4Kx2K@60fps, H.264 AVC up to 4Kx2K@30fps
	Graphic	Five core ARM Mali-450 GPU(750MHz), OpenGL ES 1.1/2.0& OpenVG 1.1
	DRAM	DRAM DDR4 2GBytes
	Network	Wi-Fi 802.11a/b/g/n/ac dual band 2T2R(optional), 10/100M Ethernet
	Bluetooth	Bluetooth 4.1
	Video output	HDMI 2.0a x1 with CEC, HDR 4Kx2K@60 with HDCP2.2
	Audio output	Audio Line Driver 2Vrms, Stereo Left/Right
	Antennas	Wi-Fi 2T2R external cable type press antenna
Power	DC Input	DC 5V/1A
	Power	Max 4.5W
Connector	HDMI	HDMI v2.0b
	A/V	SPDIF/Stereo 3.5pi Jack
	RJ45	10/100M Ethernet
	DC input	DC Adaptor Through Micro-USB

SPEC	
OS	Linux Kernel 4.9
Browser	HTML-5 Blink Browser